

BREAKER - EB 11/20/30

For Breakup Rock, Pavement & Concrete (PNEUMATIC)



DESCRIPTION

The Energy range of standard breakers has been developed over many years with the design proven in construction & allied industries throughout the world. Powerful and manoeuvrable, the Energy pneumatic breaker has an excellent power to weight ratio. This makes it the ideal tool for a wide variety of heavy duty demolition & narrow trench work jobs.

EB-30

- Cushioned handle grips for operator comfort & productivity.
- Silencer for effective noise suppression.
- Well balanced, manoeuverable & high strike energy.
- Quick change retainer.
- Ease of use due to swivel air connection.
- Easily maintained without specialist tools.
- Drop forged components for minimum ware & maximum life.
- Built in reservoir for automatic oiling & smooth continuous operation.
- Small number of moving parts to minimise internal wear.



EB-20



EB 10

SPECIFICATION

Model	Length (mm)	Frequency (BPM)	Air Consumption (CFM)	Working Pressure (Bar / PSI)	Bore (mm)	Air House (mm)	Chuck Size (mm)	Storke (mm)	Weight (Kg)
EB11	510	1620	30	6 / 90	40	40	22	89	10.9
EB20	625	1250	48	6 / 90	57	57	32 or 28	125	21.4
EB30	650	150	65	6 / 90	57	57	32 or 28	146	32.5