LMF-GP Portable Diesel Compressors **LMF P210**

Overview

LMF-GP Portable Diesel compressors are versatile and user-friendly. Their tropical design makes them unique and versatile, they are suitable for the oil and gas, marine, engineering and petro-chemical and construction industries.



Standard Features:

- Air-cooled package
- Noise attenuation enclosure External user connections
- Low engine emissions
- Sequencing capabilities
- Integrated control systems
- Fully automated controls
- One centre lifting connection
- Tier 111 compliant



Rotary screw oil injected portable Compressor

SPECIFICATIONS	
Model	LMFP210
Compressor performance*	
Rated Pressure - bar (psig)	7((100)
Work Pressure Range -bar (psig)	4.5-7(65-100)
Normal Capacity - m3/min (cfm)	6 (210)
Compressor oil capacity - L	20
Engine Detail (Typical)	
Manufacturer	CAT
Model	C2.2 DIT
Rate Speed, Full load/Idle - rpm	2520/1600
Horsepower 0 kW(BHP)	44.7 (60)
Cylinders	4
Displacement - L(in ³)	2.2
Fuel rate 0 L/h (100% load)	11.9
Coolant Capacity - L	10
Engine oil Capacity - L	10
Fuel tank Capacity - L	75
Working Voltage -Volt	12
Dimensions & Weights w/Enclosure Air-cooled Series	
Length - mm (inches)	3050 (120.1)
Width - mm (inches)	1565 (61.6)
Height - mm (inches)	1450 (57.1)
Weight - kg (lbs)	896 (1975)
Discharge Connection (Qty)	NPT3/4(2)
dBA Ratings at 7 Meter (Typical)	
Air – cooled w/ enclosure	82

