

Floor saw FSD1274

Cutting depth up to 480 mm





Maximum power transmission by means of built-in longitudinal engine with angle gear box



Saw blade coupling and neutral position mechanism for increased safety

Floor saw with powerful and economical, built-in longitudinal 74 PS Kubota turbo diesel engine. The cutting shaft in the oil bath minimises maintenance work and protects the belts from slurry. An automatic On/

Off function simplifies handling and reduces cooling water consumption. The hydraulic drive system with no belts or chains to adjust and the hydraulic handle adjustment ensure effortless and time-saving work.



System & Accessories

Saw blade

Saw blade	Standard	Maximal
Saw blade	Standard	Maximai
Max. cutting depth	230 mm	480 mm
Max. saw blade Ø	600 mm	1 200 mm
Saw blade speed	1 590 1/min	880 1/min
Saw blade holder Ø	25.4 mm	
Carrier Ø	11.5 mm	
Reference circle Ø	57.4 mm	

Drive

Drive / motor	Diesel	
Туре	Kubota	
Output	55 kW / 74 HP	
Fuel	Diesel	
Fuel tank	34.2	
Engine cooling	Water cooling	
Feed	Hydraulic	
Blade drive	Directly flange-mounted angular gear	
Feed speed	0–76 m/min	

Design

Electro-hydraulic cutting depth adjustment
Electro-mechanical cutting depth stop
Hydraulic adjustable handles
Blade clutch
Tool cooling using water fork
Left / right cutting function

Dimensions & Weight	Standard	Maximal
Length	1 615 mm	
Width	927 mm	
Height	1 335 mm	
Weight	937 kg	1 010 kg

System & Accessories

Floor saw FSD1274		
10985200	Floor saw FSD1274 (Standard configuration)	
Accessories		
10990243	Green concrete kit with 500 mm blade guard and transformation set (2 100 1/min) Max. saw blade Ø 500 mm	
10990244	900 mm blade guard and transformation set (1 165 1/min) Max. saw blade Ø 900 mm	
10990245	1 200 mm blade guard and transformation set (880 1/min) Max. saw blade \varnothing 1 200 mm	

Diesel particle filter and transformation set on request

